



Sustainability of functional DLC coatings onto thin polymers for food and electronic device packaging

Roy, SS., Mukherjee, D., Mathur, A., & McLaughlin, JAD. (2009). Sustainability of functional DLC coatings onto thin polymers for food and electronic device packaging. In *Unknown Host Publication* Unknown Publisher.

[Link to publication record in Ulster University Research Portal](#)

Published in:
Unknown Host Publication

Publication Status:
Published (in print/issue): 01/01/2009

Document Version
Publisher's PDF, also known as Version of record

General rights
Copyright for the publications made accessible via Ulster University's Research Portal is retained by the author(s) and / or other copyright owners and it is a condition of accessing these publications that users recognise and abide by the legal requirements associated with these rights.

Take down policy
The Research Portal is Ulster University's institutional repository that provides access to Ulster's research outputs. Every effort has been made to ensure that content in the Research Portal does not infringe any person's rights, or applicable UK laws. If you discover content in the Research Portal that you believe breaches copyright or violates any law, please contact pure-support@ulster.ac.uk.

Suitability of functional DLC coatings onto thin polymers for food packaging

S. S. Roy, D. Mukherjee, A. Mathur and J. A. McLaughlin

Nanotechnology and Integrated Bio-Engineering Centre (NIBEC), University of Ulster at Jordanstown,
Shore Road, BT37 0QB, Northern Ireland, United Kingdom

Functional diamond-like carbon (DLC) films (a-C:H: a-C:H:Si, a-C:H:N, ta-C:N) were deposited on polyethylene terephthalate (PET), polycarbonate (PC) and polytetrafluoroethylene (PTFE) substrates (thickness 100-500 micron) using radio frequency plasma-enhanced chemical vapour deposition (PECVD) method. We aim to highlight the optimum deposition conditions for improved gas (O₂, CO₂, etc) barrier performance of these coating. The XPS, Raman, surface profilometry, SEM and gas permeation analysis were used to analyse the microstructure and properties of the coatings. The influence of the substrate bias, film thickness, N₂ plasma pre-treatment and process pressure on the gas barrier property were reported. The hydrogen content in the coatings plays a major role in modifying their gas barrier performance. However, these hydrogen rich polymeric coatings will suffer from low hardness and weaker scratch resistance. Therefore, we have incorporated a nitrogen doping strategy to release the stress in these coatings without affecting their mechanical properties. The a-C:H:Si and a-C:H:N (with approximately 5 at % N) coatings revealed best gas barrier value of around 30 cc/m²/day/bar. Our results showed clear improvements in gas barrier properties in all of the DLC coatings in comparison to the pristine polymer substrate. It is our view that our results on thin polymer substrates are significant particularly for food packaging applications.